

MULTICOAT



CARE AND CLEANING

CARE and CLEANING *of* *SURFACES COATED WITH MULTICOAT SYSTEMS*

AFTER MULTICOAT SYSTEM HAS BEEN APPLIED:

MULTICOAT concrete overlay and Above Grade Metal Lathe Systems require sufficient time to cure. Foot traffic should be avoided for the first 24 hours after the deck has been completed. Patio furniture, potted plants, etc. should not be placed directly over the completed system for at least one week (potted plants should be put on adequate stands above the deck not directly on the deck surface). During the first two weeks after installation, care should be used to promptly remove any leaves that fall onto the surface.

MAINTENANCE:

Periodic cleaning is required. A garden hose with a jet nozzle is ideal for washing down the MULTICOAT surface when dirt, leaves, etc. are found on the deck. Most stains can be removed with powder dishwashing detergent diluted with water. Scrub vigorously with a stiff nylon bristle brush and rinse off thoroughly. Stains that cannot be removed in this manner may require a very light acid wash and neutralization with soda ash. (THIS METHOD REQUIRES PROFESSIONAL ASSISTANCE. IT IS NOT RECOMMENDED FOR USE BY PERSONS UNFAMILIAR WITH ACID WASHING METHODS.) If there are stubborn tire marks or grease stains, use a light solution of TRI-SODIUM PHOSPHATE (TSP). Scrub with nylon brush. Immediately rinse off all cleaning solution. Do not allow cleaner time to soak into surface!!

MAINTAINABILITY:

There is no warranty regarding maintainability of the MULTICOAT surface, expressed or implied. However, the recommendations listed above are made in good faith by MULTICOAT CORPORATION.

Rev. 12/1/17